



CAT.6A Keystone Jack, UTP

Art no.: NK4028

Technical Features

CAT.6A Class EA 500MHz, Unshielded


180° toolless, 17.4mm width

For AWG22-26 solid and stranded wire

ISO/IEC 11801 & TIA/EIA 568-C

Color: White/Black

Technical Drawings



Unit: mm

Electrical Characteristics:

a. Electrical

1. Contact Resistance: 20MΩ max.
2. Current Rating: 1.5 Amps
3. Insulation Resistance: 500MΩ min. @500V DC
4. Withstand Voltage: DC 1000V AC700V RMS 60Hz, 1min
5. Cat.6A Permanent Link: Conform to ANSI/TIA 568-C.2:2009 ISO 11801 CLASS EA

b. Environmental

1. Storage Temperature: -40°C ~70°C
2. Operation Temperature: -10°C ~60°C

c. Mechanical

1. Unshield Material: PC
2. IDC Material: PC Terminal: Phosphor bronze, tin plating
3. RJ45 Contact Life: 750 times min.
4. IDC Life: 250 times min.
5. Support PoE per IEEE802.3af, POE+ per IEEE802.3at

NK4028



4 052792 061796

Made in China

www.logilink.com



RoHS
compliant


*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Package Contents

1 x CAT.6A Keystone Jack, UTP

Packaging Informations

Packing Dimension	80x120 mm
Packing Weight	0.0144 kg
Carton Dimension	570x350x230 mm
Carton Q'ty	500 pcs
Carton Weight	8.5 kg



NK4028



4 052792 061796

Made in China

www.logilink.com



RoHS
compliant

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.